

# Material Safety Data Sheet

## Floor Dry

### I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Floor Dry  
 Chemical Name: HYDROUS MAGNESIUM ALUMINUM SILICATE  
 Chemical Family: ATTAPULGITE  
 Chemical Formula: N/A  
 Synonyms:

Date Revised: 7/2010  
 CAS#: 12174-11-7

NFPA Properties: Health: NDA Flammability: NDA Reactivity: NDA Contact: NDA

### Supplier:

**NOV FluidControl**  
 4310 N. Sam Houston Parkway E  
 Houston, TX 77032  
 Office: (713) 482-0500  
 Fax: (713) 482-0695  
 Company website: [www.nov.com](http://www.nov.com)

### Emergency Telephone Number:

**CHEMTREC: 1-800-424-9300 or International +1-703-527-3887**

### II. HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	TWAPPM	TWA MG/M <sup>3</sup>	TLV's (ACGIH)		CAS#	OTHER LIMITS	%
			STEL PPM	STEL MG/M <sup>3</sup>			
1. SILICA, CRYSTALLINE (QUARTZ)		0.1			14808-60-7		>1
2.							
3.							

### III. PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point °F: N/A  
 Specific Gravity: 2.35  
 Vapor Pressure: NDA  
 Percent Volatility: NDA  
 Vapor Density: N/A  
 Evaporation Rate: N/A  
 Solubility In Water: INSOLUBLE  
 Melting Point °F: N/A

Color: TAN TO GRAY  
 Odor: NONE  
 Appearance: SIZED PARTICLES  
 pH:  
 Viscosity: N/A  
 Activity: N/A  
 LC50: N/A  
 LD50: N/A

## Floor Dry

## Material Safety Data Sheet

### IV. FIRE & EXPLOSION HAZARD DATA

---

Extinguishing Agents: DRY CHEMICAL OR WATERSPRAY OR WATERFOG OR CO2 OR FOAM OR SAND & EARTH

Flash Point °F: NON-FLAMMABLE

Flammable Limits: N/A

LEL: N/A UEL: N/A

Special Firefighting Procedures: FIREFIGHTERS SHOULD WEAR PROPER PROTECTIVE EQUIPMENT AND SELFCONTAINED

(POSITIVE PRESSURE IF AVAILABLE) BREATHING APPARATUS WITH FULL FACEPIECE.

Unusual Fire & Explosion Hazards: NONE

Toxic Gases Produced: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN

### V. HEALTH HAZARD DATA

---

**Routes of Entry:** Inhalation: YES Skin: YES Ingestion: YES

Effects of Overexposure: DUST MAY IRRITATE EYES OR SKIN. AGGRAVATES PRE-EXISTING CONDITION SUCH AS ASTHMA. REPEATED INHALATION OVER EXTENDED PERIOD OF ANY DUST, INCLUDING ATTAPULGITE, IN EXCESS OF TLV MAY RESULT IN LUNG INJURY.

Toxicological Properties: NDA

Chronic & Acute Effects of Overexposure: AGGRAVATES PRE-EXISTING CONDITION SUCH AS ASTHMA. REPEATED INHALATION OVER EXTENDED PERIOD OF ANY DUST, INCLUDING ATTAPULGITE, IN EXCESS OF TLV MAY RESULT IN LUNG INJURY.

Carcinogenicity: NTP: NO IARC Monographs: YES (VOL. 42 (1987) OSHA Regulated: NO

#### **Emergency First Aid Procedures**

Eyes: IMMEDIATELY FLUSH WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES AND CALL A PHYSICIAN.

Skin Contact: FLUSH WITH LARGE AMOUNTS OF SOAP & WATER FOR 15 MINUTES.

Inhalation: REMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT, GIVE OXYGEN AND CALL A PHYSICIAN.

Ingestion: GIVE LARGE AMOUNTS OF WATER AND CALL A PHYSICIAN.

### VI. REACTIVITY DATA

---

**Stability: STABLE**

**Hazardous Polymerization: WILL NOT OCCUR**

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES, SMOKE, FUMES, OXIDES OF NITROGEN

Conditions To Avoid: HEAT, HUMIDITY

Incompatibility and Materials to Avoid: NDA

## Floor Dry

## Material Safety Data Sheet

### VII. SPILL & DISPOSAL PROCEDURES

---

Steps To Be Taken in Case Material is Released or Spilled --- Procedures For Clean – Up: WEAR SUITABLE PROTECTIVE CLOTHING. SWEEP UP WITH CLEAN EQUIPMENT AND PLACE IN APPROPRIATE CONTAINER.  
Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.  
Precautions To Be Taken In Handling & Storage: NONE

### VIII. PROTECTIVE EQUIPMENT

---

Ventilation Type Required: MECHANICAL  
Protective Gloves: RUBBER OR PLASTIC  
Respiratory Protection: WEAR A NIOSH APPROVED MASK IF CONCENTRATION IS TO EXCEED TLV  
Other Protective Equipment:  
Comments:

### IX. COMMENTS INFORMATION

---

US DOT Proper Shipping Name: "OIL – WELL TREATING COMPOUND"  
US DOT Hazard Class: DOT ID Number:  
ID Number: Freight Classification:  
Unregulated By DOT: Regulated by DOT: NO  
Special Transportation Note:  
Labels Required:

#### DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, NOV FluidControl, makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving this MSDS will make own determination as to its suitability for their intended purpose prior to use. Since the product is within the exclusive control of the user, it is the user's obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal Regulations concerning the Product. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HERUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

For further information contact:

**NOV FluidControl**  
4310 N Sam Houston Parkway East  
Houston, Texas 77032 USA  
Office: (713) 482-0500  
Fax: (713) 482-0695  
Company website: [www.nov.com](http://www.nov.com)